

# M40

MULTI-GAS MONITOR



Monitor shown actual size

Industrial Scientific is pleased to offer the M40, a versatile multi-gas monitor capable of detecting CO, H<sub>2</sub>S, O<sub>2</sub>, and combustible gases for a wide variety of hazardous and confined space applications.

The M40 is housed in a rugged, impact-resistant case to provide superior performance and durability in harsh environments and resistance to radio-frequency and electromagnetic interference. Its four-button interface provides simple, intuitive operation and calibration and the M40's five-second "Off" feature prevents unintentional shut-offs. The unit's compact size and economical price make it an ideal personal monitoring instrument.

Other standard features include a vibrating alarm, lithium-ion battery, peak/hold readings, large LCD, 50 hour datalogging capacity, and belt clip. An optional compact parasitic sampling pump enables remote sampling from up to 50 feet away. The M40 carries a 2-year warranty.

- 1 to 4 gas monitoring for O<sub>2</sub>, H<sub>2</sub>S, CO & combustible gases
- 18-hour runtime with lithium-ion battery
- Includes vibrating, 90dB audible, and LED visual alarms
- Two-year, all inclusive warranty

## SPECIFICATIONS

<b>CASE:</b>	High-visibility, impact resistant composite - RFI, EMI and IP65 tested and approved	<b>RUNTIME:</b>	18 hour - instrument (non-alarm) 12 hour - instrument with pump (non-alarm)
<b>DIMENSIONS:</b>	4.30"h x 2.45"w x 1.37"d (10.9cm x 6.22cm x 3.48cm)	<b>DISPLAY:</b>	Large LCD provides simultaneous and continuous readout of up to all four gases. Large, high-contrast characters, graphic icons and unique amber backlight provide clear display visibility in low-light conditions.
<b>WEIGHT:</b>	8.6 ounces (244 g). Weight with pump: 11.6 ounces (326 g).	<b>ALARMS:</b>	Vibrating, 90 dB audible and ultra-bright LED visual alarms. High/low, STEL, TWA, and low battery alarms. Flow alarm indicator when used with optional SP40 pump.
<b>SENSORS:</b>	The M40 is available in a 1, 2, 3, or 4-gas configuration including oxygen, hydrogen sulfide, carbon monoxide, and combustibles /hydrocarbons.	<b>DATALOGGING:</b>	Up to 50 hours of datalogging capability
<b>MEASURING RANGES:</b>	<b>CO</b> range: 0-999 ppm in 1 ppm increments <b>H<sub>2</sub>S</b> range: 0-500 ppm in 1 ppm increments <b>O<sub>2</sub></b> range: 0-30% volume in 0.1% increments <b>Combustibles:</b> 0-100% LEL in 0.1% increments The M40 features LEL over-range protection	<b>TEMPERATURE RANGE:</b>	-4° to 122°F (-20° to 50°C)
<b>POWER SOURCE:</b>	Lithium-ion battery (can be charged in instrument)	<b>HUMIDITY RANGE:</b>	15 to 95% RH, typical, 0 to 99% RH intermittent (non-condensing)
		<b>APPROVALS:</b>	UL approved - Class I, Group A, B, C, D CSA (pending) - Class I, Group A, B, C, D Cenelec (ATEX) and Australia - EEx ia IIc T4 (pending)

REV0903

**INDUSTRIAL SCIENTIFIC**  
**CORPORATION**

1001 Oakdale Road, Oakdale, PA 15071-1500  
(412) 788-4353 Toll Free: 1-800-DETECTS Fax: (412) 788-8353 www.indsci.com e-mail: info@indsci.com

Industrial Scientific is an Equal Opportunity Employer.



## M40 COMMON CONFIGURATIONS AND OPTIONAL ACCESSORIES

PART NUMBER	DESCRIPTION
18105437-01111*	<b>M40</b> - Four gas configuration for O <sub>2</sub> , LEL, CO, H <sub>2</sub> S
18105437-01110*	<b>M40</b> - Three gas configuration for O <sub>2</sub> , LEL, H <sub>2</sub> S
18105437-01101*	<b>M40</b> - Three gas configuration for O <sub>2</sub> , LEL, CO
18105437-00110*	<b>M40</b> - Two gas configuration for H <sub>2</sub> S, LEL
18105437-01100*	<b>M40</b> - Two gas configuration for O <sub>2</sub> , LEL
18105437-00100*	<b>M40</b> - Combustible gas configuration for LEL only
18105437-11111 <sup>+</sup>	<b>M40 and Pump</b> Combination for O <sub>2</sub> , LEL, CO, H <sub>2</sub> S
18105437-11110 <sup>+</sup>	<b>M40 and Pump</b> Combination for O <sub>2</sub> , LEL, H <sub>2</sub> S
18105437-11101 <sup>+</sup>	<b>M40 and Pump</b> Combination for O <sub>2</sub> , LEL, CO
18105437-11100 <sup>+</sup>	<b>M40 and Pump</b> Combination for O <sub>2</sub> , LEL
18105437-10100 <sup>+</sup>	<b>M40 and Pump</b> Combination for LEL
M40-KIT-11111**	<b>M40 Confined Space Kit</b> (with Pump) - O <sub>2</sub> , LEL, CO, H <sub>2</sub> S
M40-KIT-11101**	<b>M40 Confined Space Kit</b> (with Pump) - O <sub>2</sub> , LEL, CO
M40-KIT-11110**	<b>M40 Confined Space Kit</b> (with Pump) - O <sub>2</sub> , LEL, H <sub>2</sub> S
18105460	<b>SP40 Sampling Pump</b>
18105528	M40 Datalink
18105478	M40 Nylon Carrying Case
18105486	M40/SP40 Combination Carrying Case
18105494	Compact Charger 120 VAC
18105668	Compact Charger 230 VAC
18105890	UK Compact Charger 230 VAC
18105908	AUS Compact Charger 230 VAC
18105502	12 VDC Automotive Charger
18105510	6 Unit Charger
17092941	Metal Belt Clip
17107582	Suspender Clip



M40 Multi-Gas Monitor shown with optional SP40 Sampling Pump

**\*All monitors include:**

- choice of charger
- calibration cup
- tubing
- nylon carrying case
- cell-phone style belt clip
- maintenance tool
- instruction manual

**++All monitor/pump combinations include:**

- choice of charger
- calibration cup
- tubing
- cell-phone style belt clip
- maintenance tool
- instruction manual
- combo monitor/pump nylon carrying case

**\*\*All confined space kit combinations include:**

- choice of charger
- calibration cup
- tubing
- utility case
- gas cylinder
- cell-phone style belt clip
- maintenance tool
- regulator valve
- water barrier assembly
- filter
- instruction manual
- combo monitor/pump nylon carrying case